

HARNESS-LIGHTING,INTERIOR

WIRE COLOR LEGEND

BG	BEIGE (TAN)
BK	BLACK
BU	LIGHT BLUE
DB	DARK BLUE
BN	BROWN
GY	GRAY
GN	LIGHT GREEN
DG	DARK GREEN
OG	ORANGE
PK	PINK
RD	RED
VT	VIOLET (PURPLE)
WH	WHITE
YE	YELLOW
CL	CLEAR

TWO WIRE COLORS ARE SHOWN WITH MAIN/TRACE COLORS. EXAMPLE:RD/YE = RED WITH YELLOW TRACE.

E

≠

ENGINE GROUND

C

≠

CHASSIS GROUND

NC = SWITCH NORMALLY CLOSED

NO = SWITCH NORMALLY OPEN

Line No.	CCT#	GROUPING	TYPE	GAUGE	COLOR	FROM COMPONENT	FROM PORT	TO COMPONENT	TO PORT	FUNCTION
1	FU101-6		TXL	0.35	RD/DB	INT ACCENT LIGHT, LH		SPLICE, ACCESSORY	2	INSTR ACCY FUSE, LH ACCENT LT
2	FU101-7		TXL	0.35	RD/DB	SPLICE, LED CTR, ANODE RED	1	SPLICE, ACCESSORY	2	INSTR ACCY FUSE, CTR LED
3	FU101-8		TXL	0.35	RD/DB	INT ACCENT LIGHT, RH	1	SPLICE, ACCESSORY	2	INSTR ACCY FUSE, RH ACCENT LT
4	FU1015		TXL	0.8	RD/DB	CHASSIS INTERFACE	B	SPLICE, ACCESSORY	1	ACCESSORY RELAY
5	GF4-5		TXL	0.35	BN	INT ACCENT LIGHT, LH	2	SPLICE, GROUND	2	GROUND, INT ACCENT LT, LH
6	GF4-6		TXL	0.35	BN	SPLICE, LED CTR, CATHODE BLACK	1	SPLICE, GROUND	2	GROUND, CTR LED
7	GF4-7		TXL	0.35	BN	INT ACCENT LIGHT, RH	2	SPLICE, GROUND	2	GROUND, INT ACCENT LT, RH
8	GF23		TXL	0.8	BN	SPLICE, GROUND	1	CHASSIS INTERFACE	C	GROUND, CHASSIS INTERFACE

CHASSIS INTERFACE

GF23 BN 0.8 — SPLICE, GROUND — GROUND, CHASSIS INTERFACE — CHASSIS INTERFACE PIN:H

GF4-7 BN 0.35 — GROUND, INT ACCENT LT, RH — INT ACCENT LIGHT, RH PIN:2

GF4-5 BN 0.35 — GROUND, INT ACCENT LT, LH — INT ACCENT LIGHT, LH PIN:2

GF4-6 BN 0.35 — GROUND, CTR LED — SPLICE, LED CTR, CATHODE BLACK PIN:1

SPLICE, GROUND PIN:1 — GROUND, CHASSIS INTERFACE — GF23 BN 0.8

SPLICE, ACCESSORY PIN:1 — ACCESSORY RELAY — FU1015 RD/DB 0.8

INT ACCENT LIGHT, LH

SPLICE, GROUND PIN:2 — GROUND, INT ACCENT LT, LH — GF4-5 BN 0.35

SPLICE, ACCESSORY PIN:2 — INSTR ACCY FUSE, LH ACCENT LT — FU101-6 RD/DB 0.35

INT ACCENT LIGHT, RH

SPLICE, GROUND PIN:2 — GROUND, INT ACCENT LT, RH — GF4-7 BN 0.35

SPLICE, ACCESSORY PIN:2 — INSTR ACCY FUSE, RH ACCENT LT — FU101-8 RD/DB 0.35

SPLICE, LED CTR, CATHODE BLACK

SPLICE, GROUND PIN:2 — GROUND, CTR LED — GF4-6 BN 0.35

SPLICE, LED CTR, ANODE RED

SPLICE, ACCESSORY PIN:2 — INSTR ACCY FUSE, CTR LED — FU101-7 RD/DB 0.35

5

4

3

2

1